

Newmans Enclosed Gran Prix Recreational Trailer

www.newmansinc.com

17', 21', 23', 25' & 27' Tandem Axle Models

Standard Features:

- Maintenance-free all aluminum construction
- .040 painted sheeting
- Built-in tie-down system
- Two 3500# Dexter torsion axle with EZ Lube hubs
- 3/4" marine plywood decking
- Electric brakes on all axles for added security
- 2^{5/16}-inch ball coupler with coated safety cables
- Spring-assisted rear and v-ramp doors
- 16" center (roof, sides, floor)
- Kick board
- 24" aluminum stone guard
- Jack stand
- 15" steel wheels



207 S Hwy 10, P.O. Box 24 • Royalton, MN 56373 • Phone: 320-584-5506 • Fax: 320-584-6391

Newmans Enclosed Gran Prix Trailer Specification Chart

	1EN817V	1EN821V	1EN823V	1EN825V	1EN827V
Total Dimensions:					
Length	204"	252"	276"	300"	324"
Width (body)	83"	101"	101"	101"	101"
Height	96 ^{1/2} "	96 ^{1/2} "	96 ^{1/2} "	96 ^{1/2} "	96 ^{1/2} "
Interior Dimensions:					
Length	199"	247"	271"	295"	319"
Length (excluding v-front)	144"	192"	216"	240"	264"
Width	99"	99"	99"	99"	99"
Height	73"	73"	73"	73"	73"
Platform Height:	22"	22"	22"	22"	22"
Axles:					
Quantity	2	2	2	2	2
Type	Dexter®	Dexter®	Dexter®	Dexter®	Dexter®
Brakes	electric	electric	electric	electric	electric
Tire Size:	H78-15ST	H78-15ST	H78-15ST	H78-15ST	H78-15ST
Load Range:	D	D	D	D	D
Wheel Style:	steel mod	steel mod	steel mod	steel mod	steel mod
Wheel Bolt Pattern:	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Hitch Ball Size:	2 ^{5/16} "	2 ^{5/16} "	2 ^{5/16} "	2 ^{5/16} "	2 ^{5/16} "
Curb Weight (estimated lbs.)	2314	2443	2518	2565	2650
GVWR (lbs.)	7000	7000	7000	7000	7000
GAWR (lbs.)	7000	7000	7000	7000	7000
Payload Capacity (lbs.)	4686	4557	4482	4435	4350
Rear Ramp Door:					
Height	70 ^{1/2} "	70 ^{1/2} "	70 ^{1/2} "	70 ^{1/2} "	70 ^{1/2} "
Width	92"	92"	92"	92"	92"
Beavertail	none	none	none	none	none
Front Ramp Door:					
Height	69 ^{3/4} "	69 ^{3/4} "	69 ^{3/4} "	69 ^{3/4} "	69 ^{3/4} "
Width	64 ^{1/2} "	64 ^{1/2} "	64 ^{1/2} "	64 ^{1/2} "	64 ^{1/2} "