

Newmans Enclosed In-Line Recreational Trailer

www.newmansinc.com

17', 21', 23' & 27' Tandem Axle Models

Standard Features:

- Maintenance-free all aluminum construction
- .040 painted sheeting
- Built-in tie-down system
- Two 3500# Dexter torsion axle with EZ Lube hubs
- 5/8" marine plywood decking
- Electric brakes on all axles for added security
- 2^{5/16}-inch ball coupler with coated safety cables
- Spring-assisted rear and v-ramp doors
- 16" center on sides, 24" center on roof and floor
- Kick board
- Jack stand
- 15" steel wheels



207 S Hwy 10, P.O. Box 24 • Royalton, MN 56373 • Phone: 320-584-5506 • Fax: 320-584-6391

Newmans Enclosed In-Line Trailer Specification Chart

	1EN717V	1EN721V	1EN723V	1EN727V
Total Dimensions:				
Length	204"	252"	276"	324"
Width (body)	83"	83"	83"	83"
Height	96 ^{1/2} "	96 ^{1/2} "	96 ^{1/2} "	96 ^{1/2} "
Interior Dimensions:				
Length	199"	247"	271"	319"
Length (excluding v-front)	144"	192"	216"	264"
Width	81"	81"	81"	81"
Height	73"	73"	73"	73"
Platform Height:	22"	22"	22"	22"
Axles:				
Quantity	2	2	2	2
Type	Dexter®	Dexter®	Dexter®	Dexter®
Brakes	electric	electric	electric	electric
Tire Size:	H78-15ST	H78-15ST	H78-15ST	H78-15ST
Load Range:	D	D	D	D
Wheel Style:	steel mod	steel mod	steel mod	steel mod
Wheel Bolt Pattern:	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Hitch Ball Size:	2 ^{5/16} "	2 ^{5/16} "	2 ^{5/16} "	2 ^{5/16} "
Curb Weight (estimated lbs.)	1556	1767	1880	2330
GVWR (lbs.)	7000	7000	7000	7000
GAWR (lbs.)	7000	7000	7000	7000
Payload Capacity (lbs.)	5444	5233	5180	4670
Rear Ramp Door:				
Height	70 ^{1/2} "	70 ^{1/2} "	70 ^{1/2} "	70 ^{1/2} "
Width	74"	74"	74"	74"
Beavertail	none	none	none	none
Front Ramp Door:				
Height	69 ^{3/4} "	69 ^{3/4} "	69 ^{3/4} "	69 ^{3/4} "
Width	64 ^{1/2} "	64 ^{1/2} "	64 ^{1/2} "	64 ^{1/2} "