

Newmans Enclosed Motorcycle Trailer

www.newmansinc.com

12' & 17' Single and Tandem Axle Models

Standard Features:

- Maintenance-free all aluminum construction
- .040 painted sheeting
- 5/8" marine plywood decking
- Spring-assisted rear ramp door
- Built-in tie-down system
- 16" center on sides, 24" center on roof and floor
- Kick board
- Wheel chocks
- 15" steel wheels

Single Axle

- Electric brakes
- 3500# Dexter torsion axle with EZ Lube hubs
- 2-inch ball coupler with coated safety cables

Tandem Axle

- Electric brakes on all axles for added security
- Two 2500# Dexter torsion axles with EZ Lube hubs
- 2^{5/16}-inch ball coupler with coated safety cables



207 S Hwy 10, P.O. Box 24 • Royalton, MN 56373 • Phone: 320-584-5506 • Fax: 320-584-6391

Newmans Enclosed Motorcycle Trailer Specification Chart

	1ENM712-5	1ENM712S-5	1ENM717V-5	1ENM717VS-5
Total Dimensions:				
Length	144"	144"	204"	204"
Width (body)	83"	83"	83"	83"
Height	81 ^{1/2} "	81 ^{1/2} "	81 ^{1/2} "	81 ^{1/2} "
Interior Dimensions:				
Length	139"	139"	199"	199"
Length (excluding v-front)	n/a	n/a	144"	144"
Width	81"	81"	81"	81"
Height	61"	61"	61"	61"
Platform Height:	19"	19"	19"	19"
Axles:				
Quantity	2	1	2	1
Type	Dexter®	Dexter®	Dexter®	Dexter®
Brakes	electric	electric	electric	electric
Tire Size:	H78-15ST	H78-15ST	H78-15ST	H78-15ST
Load Range:	D	D	D	D
Wheel Style:	steel mod	steel mod	steel mod	steel mod
Wheel Bolt Pattern:	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Hitch Ball Size:	2 ^{5/16} "	2"	2 ^{5/16} "	2"
Curb Weight (estimated lbs.)	1268	1190	1443	1354
GVWR (lbs.)	5000	3500	5000	3500
GAWR (lbs.)	5000	3500	5000	3500
Payload Capacity (lbs.)	3732	2310	3557	2146
Rear Ramp Door:				
Height	61 ^{1/4} "	61 ^{1/4} "	61 ^{1/4} "	61 ^{1/4} "
Width	74"	74"	74"	74"
Beavertail	3"	3"	3"	3"