

Newmans Enclosed Over-the-Wheels Recreational Trailer

www.newmansinc.com

17' Single Axle Model and 17', 21' & 25' Tandem Axle Models

Standard Features:

- Maintenance-free all aluminum construction
- .040 painted sheeting
- 5/8" marine plywood decking
- Spring-assisted rear and v-ramp doors
- 24" center (roof, sides, floor)
- Kick board
- Jack stand
- 13" steel wheels

Single Axle

- Electric brakes
- 3500# Dexter torsion axle with EZ Lube hubs
- 2-inch ball coupler with coated safety cables

Tandem Axle

- Electric brakes on all axles for added security
- Two 2200# or two 2500# Dexter torsion axles with EZ Lube hubs
- 2-inch ball coupler with coated safety cables



207 S Hwy 10, P.O. Box 24 • Royalton, MN 56373 • Phone: 320-584-5506 • Fax: 320-584-6391

Newmans Enclosed Over-the-Wheels Trailer Specification Chart

	1ENH817VS	1ENH817V	1ENH821V	1ENH825V
Total Dimensions:				
Length	204"	204"	252"	300"
Width (body)	101"	101"	101"	101"
Height	102"	102"	102"	102"
Interior Dimensions:				
Length	199"	199"	247"	295"
Length (excluding v-front)	144"	144"	192"	240"
Width	99"	99"	99"	99"
Height	73"	73"	73"	73"
Platform Height:	28"	28"	28"	28"
Axles:				
Quantity	1	2	2	2
Type	Dexter®	Dexter®	Dexter®	Dexter®
Brakes	electric	electric	electric	electric
Tire Size:	B78-13	B78-13	B78-13	B78-13
Load Range:	C	C	C	C
Wheel Style:	steel mod	steel mod	steel mod	steel mod
Wheel Bolt Pattern:	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Hitch Ball Size:	2"	2"	2"	2"
Curb Weight (estimated lbs.)	1525	1745	2010	2365
GVWR (lbs.)	2720	4400	5000	5000
GAWR (lbs.)	2720	4400	5000	5000
Payload Capacity (lbs.)	1195	2655	2990	2635
Rear Ramp Door:				
Height	70 ^{1/2} "	70 ^{1/2} "	70 ^{1/2} "	70 ^{1/2} "
Width	92"	92"	92"	92"
Beavertail	none	none	none	none
Front Ramp Door:				
Height	69 ^{3/4} "	69 ^{3/4} "	69 ^{3/4} "	69 ^{3/4} "
Width	64 ^{1/2} "	64 ^{1/2} "	64 ^{1/2} "	64 ^{1/2} "